



Storm Armor coil coating finishes provide a new level of Long Term Exterior performance for building product applications.

Provides superior resistance to chalking, fading and environmental weathering.

Storm Armor uses only the highest quality **Exterior Grade and Cool Pigmentation** to insure the best available long term high U.V. radiation color and gloss retention.

Offers the toughest surface available, resistant to marring, transit abrasion and scratching during installation and handling.

Available in a wide variety of standard and custom colors.

Designed to be applied as two-coat primer/finish system. Using one of the toughest primers available in the market, which enhances the performance of the overall system.

	FILM ADHESION LENGTH	FADING COVERAGE LENGTH	FADING UNITS (The lower the hunter unit, the better performance)	CHALKING COVERAGE LENGTH	CHALKING NUMBER
PVDF	40 years	40 years	5 Hunter delta- E units for roofs & walls	30 years	8 Rating roof & walls
SMP	40 years	40 years	7 Hunter delta- E units for roofs (horizontal) 5 Hunter delta-E units for walls (vertical)	30 years	6 Rating roof (horizontal) 8 Rating walls (vertical)



Storm Armor Premium Paint Coating

Commercial Grade Metal Primer

Pretreatment Layer

AZ50 Galvalume

Steel or Aluminum

AZ50 Galvalume

Pretreatment Layer

Corrosion Resistant Primer

- Premium exterior performance
- Industrial Applications
- Architectural Applications
- AAMA 2605
- Long Lasting Finish

Designed as a premium finish to provide outstanding color stability, gloss retention, exceptional abrasion resistance, chemical resistance, and great film flexibility

